

MATERIAL DATA SHEET

SELF-ADHESIVE BACKING USED ON SILICONE SHEETS AND STRIPS

Product Description: Double sided tape

Adhesive: The adhesive is a modified polyacrylic showing good adhesive properties including initial and long term adhesion with excellent shear resistance. The adhesive exhibits good plasticiser resistance when bonded to a variety of plasticised substrates and is optimised for ageing resistance and especially useful where good heat resistance is required.

| | | |
|---------------------------|------------------------|--|
| Product structure: | Support | Non-woven, 12 g/m ² |
| | Interliner | Release paper, yellow, 90 g/m ² |
| | Adhesive weight | 90 g/m ² |
| | Total thickness | 0,10 mm |

Characteristics: **Temperature resistance** from -40 °C to +200 °C
(according to the ATP test method AA-B-12-07)

Adhesive strength min 13 N/25 mm
(According to AFERA 5001) Contact time: 1 h

Issue 6

April 2018



J-FLEX

High Performance Elastomer Sheetings & Manufactured Components

Units 1 & 2, London Road Business Park, Retford,
Nottinghamshire, DN22 6HG, United Kingdom

tel: +44 (0) 1777 712 400 fax: +44 (0) 1777 712 409
www.j-flex.co.uk

